

UK DECLARATION OF PERFORMANCE
Regulation (EU) 305/2011 No. 0001 — CPR-2013/07/01



No.: 127

- | | |
|--|--|
| 1. Unique identification code of the product-type | RAIS VISIO Uniq 3-sided model - ATTIKA VISIO Uniq 3-sided Model |
| 2. Type | Inset appliance burning solid fuel without hot water supply |
| 3. Intended use | Domestic room heater |
| 4. Manufacturer | Spartherm Feuerungstechnik GmbH, Maschweg 38, D-49324 Melle, www.spartherm.com |
| 5. Authorised representative | RAIS A/S, Industrivej 20, Vangen, DK-9900 Frederikshavn, Denmark, www.rais.com / www.attika.ch |
| 6. System of assessment AVCP | System 3 |
| 7. Notified body | The notified laboratory <i>Danish Technological Institute - Identification no. 1235 Teknologiparken, Kongsvang Allé 29, DK-8000 Århus C</i>
performed the determination of the product type on the basis of type testing under system 3 and issued test report
a. 300-ELAB-2564-EN |
| 8. Declared performance | Harmonized technical specification: EN 13229:2001/A2:2004/AC:2007 |

Essential characteristics		Performance
Fire safety		- Insulated flue 50 mm Skamotec 225 non-combustible panel board Distances are measured externally on the built-in box
Reaction to fire	A1	Visio Uniq 3-sided model
Distance to combustible materials	rear	0
Minimum distances [mm]	sides	650
For other installation or wall settings see instruction manual	ceiling	250
	Front	1000
	Floor	400
Risk of burning fuel falling out	Pass	
OGC (mg/Nm ³ rel. 13 Vol-% O ₂)	57	
CO-emission of combustion products	0,07 % / 893 mg/Nm ³	
NO _x (mg/Nm ³ rel. 13 Vol-% O ₂)	113	
Dust mg/Nm ³ at (rel. 13 Vol-% O ₂)	23	
Surface temperature	Pass	
Electrical safety	NPD	
Cleanability	Pass	
Maximum operating pressure	- bar	
Flue gas temperature T at nominal heat output	228 °C	
Mechanical resistance (to carry a chimney/flue)	NPD	
Thermal output		
Nominal heat output	9,3 kW	
Room heating output	9,3 kW	
Water heating output	- kW	
Energy efficiency η	78 %	
Seasonal Efficiency $\eta_{S, on}$	68 %	

- 9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.**
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

John Engell Nielsen, R&D Manager

Place FREDERIKSHAVN, DENMARK

Date 14-09-2022


Signature