

Table 1

Model identifier(s): R600RD MAX

	Teknologisk Institut (1235)	
Indirect heating functionality: (yes/No)	No	
Direct heat output	7,9	kW
Indirect heat output:	N.A.	kW
Energieeffektivitetsindeks (EEI)	100	
Test Report	300-ELAB-2686	
Test Standard	EN13229	



Date: 31-07-2024

Fuel	Preferred fuel (only one):	Other suitable fuels(s):	seasonal space heating energy efficiency η_s [%]:	Space heating emissions at nominal heat output(*)				Space heating emissions at minimum heat output(*)(**)			
				PM	OGC	CO	NOx	PM	OGC	CO	NOx
				[x] mg/Nm ³ (13 % O ₂)				[x] mg/Nm ³ (13 % O ₂)			
Wood logs with moisture content \leq 25 %	yes	no	69	14	43	958	77	NA	NA	NA	NA
Compressed wood with moisture content < 12 %	no	no									
Other woody biomass	no	no									
Non-woody biomass	no	no									
Anthracite and dry steam coal	no	no									
Hard coke	no	no									
Low temperature coke	no	no									
Bituminous coal	no	no									
Lignite briquettes	no	no									
Peat briquettes	no	no									
Blended fossil fuel briquettes	no	no									
Other fossil fuel	no	no									
Blended biomass and fossil fuel briquettes	no	no									
Other blend of biomass and solid fuel	no	no									

(*) PM = particulate matter, OGCs = organic gaseous compounds, CO = carbon monoxide, NOx = nitrogen oxides (**) Only required if correction factors F(2) or F(3) are applied.

Characteristics when operating with the preferred fuel only

Item	Symbol	Value	Unit
------	--------	-------	------

Heat output

Nominal heat output	P_{nom}	7,9	kW
Minimum heat output (indicative)	P_{min}	NA	kW

Auxiliary electricity consumption

At nominal heat output	e_{lmax}	NA	kW
At minimum heat output	e_{lmin}	NA	kW
In standby mode	e_{lSB}	NA	kW

Permanent pilot flame power requirement

Pilot flame power requirement (if applicable)	P_{pilot}	NA	kW
-----------------------------------------------	-------------	----	----

Contact details

Rais A/S, Industrivej 20, 9900 Frederikshavn, Denmark

Homepage

www.rais.com

E-Mail

kundeservice@rais.dk

Phone

+45 98 47 90 33

Item	Symbol	Value	Unit
------	--------	-------	------

Useful efficiency (NCV as received)

Useful efficiency at nominal heat output	$\eta_{th,nom}$	79	%
Useful efficiency at minimum heat output	$\eta_{th,min}$	NA	%

Type of heat output/room temperature control (select one)

single stage heat output, no room temperature control	NO
two or more manual stages, no room temperature control	NO
with mechanic thermostat room temperature control	NO
with electronic room temperature control	NO
with electronic room temperature control plus day timer	NO
with electronic room temperature control plus week timer	NO
Other control options (multiple selections possible)	
room temperature control, with presence detection	NO
room temperature control, with open window detection	NO
with distance control option	NO